

SfAR-1M-4DI-M

SfAR-1M-4DI-M is designed for applications with flowmeters, thanks to its counting feature with saving to FRAM memory. Perfect choice for applications with a need for counting or timing of digital inputs state.

The module has 4 **digital inputs** (DI). Digital inputs can work as fast pulse **counters** with up to 1000 counts per sec, or **timers** measuring the ON state, and also offering a possibility to connect 2 **encoders**. SfAR-S-16DI-M comes with a **FRAM memory**, allowing a user to save states of counters or timers in case of power loss. Digital inputs support both **PNP** and **NPN** input types. All inputs are isolated from the RS485 and power supply.

A built-in **RS485** interface allows easy connection over **Modbus RTU/ASCII** protocol. A 32-bit ARM core processor provides fast processing and communication.

The module is equipped with a set of **LEDs** used to indicate the status of I/O, power supply, and RS485 communication.

Configuration of the modules is carried out with our free software, the **SfAR Configurator**. A built-in mini **USB** allows to perform a primary configuration of the unit without additional power supply.

Key Features

- 4 opto-isolated digital input
- Every DI can work as 32-bit pulse counters or timer
- Non-volatile FRAM memory for counters
- Support for 2 encoders
- Built-in LEDs for device status indication
- Modbus RTU/ASCII communication
- Baud rate: 2400 bps to 115200 bps
- Up to 128 modules on the bus
- Built-in mini USB type B port for configuration
- Space-saving housing, DIN rail mount



SfAR-1M-4DI-M

Specification

Digital Inputs (DI)

- PNP or NPN transistor inputs
- Fast pulse counter up to 1 kHz save to FRAM memory
- Timer
- Up to 2 encoders support
- Opto-isolated from RS485 and power supply

Platform

- ARM Cortex-M3

Communication

- RS485 interface
- Up to 128 devices on the bus
- Modbus RTU/ASCII
- Baud rate: 2400 to 115200 bps
- Mini USB type B
- Built-in LED indicators
- Free software: SfAR Configurator

Power Supply

- 10-38 V DC; 10-28 V AC

Housing

- Dimensions WxHxD: 17x90x56 mm
- Construction: UL approved, self-extinguishing plastic (PC/ABS)
- DIN rail mounting DIN (DIN EN 50022 norm)
- Cooling: internal air circulation

Environment

- Operating temperature: -10°C to 50°C
- Storage temperature: -40°C to 85°C
- Relative humidity: 5% to 95%, no condensation
- Ingress protection rating: IP40 – for indoor installation

Dimensions

